

## OVERVIEW

**Handycoat DP is a dry powder non hydraulic filler for use as a skim coat and jointing compound for gypsum boards. It gives a high quality, even surface for painting. Handycoat DP is specially manufactured for the painter to repair and touch up interior surface, both old and new, prior to painting. Handycoat DP fills joints and hairline cracks etc. Unlike conventional fillers Handycoat DP has plastic properties, does not flake off, is permanent and retains its adhesion.**

## PROPERTIES

Handycoat DP is made from a selected blend of acrylic polymers and precisely graded fillers. It is:

- Easy to mix by hand.
- Does not flake off.
- Has high adhesion power.
- Applicable up to 4mm in thickness.
- Has high coverage.
- Quick drying.
- Vapour permeable.

## BONDING

When dry, Handycoat DP bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplasters, wood, galvanised steel lathings and all common building surface.

If the surface on which Handycoat DP is to be applied shows signs of flaking or dusting, then the surface should be cleaned thoroughly and TERRACO Penetrating Primer or Terrabond applied prior to patching with Handycoat DP.

Surface affected by rising damp should be treated with a damp-proofing system prior to application of filler. If damp is constant danger then the use of TERRACO Acrylic Filler is recommended.

## AREA OF USE

Ideal as a gypsum board jointing compound and skimcoat, for patching hairline cracks in walls, ceilings, repairing damage to plaster/paint work, nail holes in woodwork, making good around door architrave's and along the top of skirtings etc.

## PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Ridges and oil must be also removed. The use of Terraco Penetrating Primer is recommended on dusting or flaking surfaces.

When applying Handycoat DP to old painted surfaces first wash down with soda / water solution, rinse and allow to dry before application of Handycoat DP.

## MIXING

Mix 20kg of Handycoat DP with 8kg water using a high speed mixer and allow to stand for 5 minutes before use.

## APPLICATION & CLEANING OF TOOLS

Apply the Handycoat DP in a thin even layer and allow to dry. Apply a second coat if necessary to achieve a level surface.

Lightly sandpaper over the dry final surface before painting preferably within 24 hours of application.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING & STORAGE

Handycoat DP is supplied 20 kg paper bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

## TECHNICAL DATA

<b>Product</b>	Dry powder skim coat and jointing compound for gypsum board.
<b>Filler</b>	Precisely graded marble.
<b>Binder</b>	Vinyl acetate copolymer.
<b>Mixing</b>	20kg Handycoat DP/ 8kg water.
<b>Colour</b>	White.
<b>Standard</b>	ASTM C475
<b>Shrinkage</b>	Negligible.
<b>Application</b>	By spatula.
<b>Average Consumption</b>	1.25kg/m <sup>2</sup> /mm thickness depending upon surface conditions.
<b>Toxicity</b>	Non-toxic
<b>Packaging</b>	20kg paper bags.
<b>Storage</b>	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

### CHINA:

**Terraco Architectural Coatings China Co., Ltd.**  
 Tel: +86 (0)20 8759 4742  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

**Terraco Chemical (Shanghai) Co., Ltd.**  
 Tel: +86 (0)21 621020 48 / 18  
 Fax: +86 (0)21 625205 47  
 Email: sales@terraco.com.cn  
 Web: www.terraco.com.cn

### EGYPT:

**Terraco Egypt Chemical Industries S.A.E.**  
 Tel: +20 (0)22 29184 53 / 57 / 58  
 Fax: +20 (0)22 29184 80  
 E-mail: terraco@terraco.com.eg  
 Web: www.terraco.com.eg

### JORDAN:

**Jordan Swedish Polymers Industrial Corp.**  
 Tel: +962 (0)6 553 8751  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

### IRELAND:

**Terraco Technical Centre, Ireland**  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: technical-centre@terraco.com  
 Web: www.terraco.com

### PAKISTAN:

**Terraco Pakistan Pvt. Ltd.**  
 Tel: +92 (0)42 3529 70 56-8  
 Fax: +92 (0)42 3529 70 55  
 Email: terraco@terraco.pk  
 Web: www.terraco.com

### ROMANIA:

**Terraco Romania SRL**  
 Tel: +40 (0)749 203 133  
 Fax: +40 (0)318 148 810  
 E-mail: ahaque@terraco.com  
 Web: www.terraco.com

### RUSSIA:

**OOO Terraco Sweden Ltd, Russia**  
 Tel: +7 (0)495 9212 237  
 Fax: +7 (0)495 6273 881  
 E-mail: adm@terraco.ru  
 Web: www.terraco.ru

### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563  
 Fax: +7 (0)4212 410591  
 E-mail: terracovostok@terraco.khn.ru  
 Web: www.terraco.com

### SOUTH KOREA:

**Terraco Korea Co., Ltd**  
 Tel: +82 (0) 2 5611 551  
 Fax: +82 (0)2 5671 771  
 E-mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

### THAILAND:

**Terraco Industry (Thailand) Limited**  
 Tel: +66 (0)2 946 68 56 / 58  
 Fax: +66 (0)2 946 68 59  
 E-mail: terraco@terraco.co.th  
 Web: www.terraco.com

### TURKEY:

**Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS**  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

### UAE:

**Terraco UAE Ltd**  
 Tel: +971 (0)4 326 2699  
 Fax: +971 (0)4 326 2733  
 E-mail: terraco@terraco.ae  
 Web: www.terraco.com

### UK:

**ADDAGRIP**  
 Tel: +44 (0)1825 761 333  
 Fax: +44 (0)1825 768 566  
 E-mail: sales@addagrip.co.uk  
 Web: www.addagrip.co.uk / www.terraco.com

### VIETNAM:

**Terraco Vietnam Co., Ltd**  
 Tel: +84 (0)650 3 820 100  
 Fax: +84 (0)650 3 820101  
 E-mail: terraco@terraco.com.vn  
 Web: www.terraco.com