

OVERVIEW

Maxi Gypsum Jointing Compound is a ready to use filler for use as a skim-coat and jointing compound for gypsum boards, it gives a high quality, even surface for painting. Maxi Gypsum Jointing Compound is also suitable to repair and touch up most interior surfaces, both old and new, prior to painting. Maxi Gypsum Jointing Compound fills joints and hairline cracks, etc. Unlike conventional fillers Maxi Gypsum Jointing Compound has plastic properties, does not flake off, is permanent and retains its adhesion.

PROPERTIES

Maxi Gypsum Jointing Compound is made from a selected blend of polymers and graded fillers. It has the following properties.

- Easy to use
- Easy to sand
- Quick drying
- Good adhesion
- Good jointing properties
- Vapour permeable

AREAS OF USE

Maxi Gypsum Jointing Compound is used as a skim-coat or a jointing compound for gypsum boards.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Ridges and form oil must also be removed. The use of Terraco Penetrating Primer is recommended on dusting or flaking surfaces.

When applying Maxi Gypsum Jointing Compound to old painted surfaces, first wash down with soda/water solution, rinse and allow to dry before application of Maxi Gypsum Jointing Compound.

Fix self adhesive fiberglass tape to board joints.

PRIMING

To stabilise a surface which shows signs of flaking or dusting the use of Terraco Penetrating Primer is recommended.

APPLICATION & CLEANING OF TOOLS

Apply Maxi Gypsum Jointing Compound in a thin layer and allow to dry. Apply a second coat, if necessary to achieve full leveling.

Lightly sandpaper over the dry final surface before painting preferably within 24 hours of application.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Maxi Gypsum Jointing Compound is supplied in 5kg and 28kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Ready-mixed quick drying filler of inert extenders,
Binder	Vinyl co-polymer.
Fillers	Precisely graded marble.
Dilution	Water if required.
Average Consumption	0.5-1.5kg/m ² , depending on substrate conditions.
Density	1.75 ± 0.05
Application	By spatula.
Colour	Natural white
Durability	Negligible shrinkage
Toxicity	Non-toxic.
Standard of Compliance	ASTM C475
Packaging	5kg and 28kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 621020 48 / 18
 Fax: +86 (0)21 625205 47
 Email: sales@terraco.com.cn
 Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)22 29184 53 / 57 / 58
 Fax: +20 (0)22 29184 80
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 553 8751
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: technical-centre@terraco.com
 Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.
 Tel: +92 (0)42 3529 70 56-8
 Fax: +92 (0)42 3529 70 55
 Email: terraco@terraco.pk
 Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 (0)495 9212 237
 Fax: +7 (0)495 6273 881
 E-mail: adm@terraco.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracovostok@terraco.kh.vu
 Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611 551
 Fax: +82 (0)2 5671 771
 E-mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 946 68 56 / 58
 Fax: +66 (0)2 946 68 59
 E-mail: terraco@terraco.co.th
 Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd
 Tel: +971 (0)4 326 2699
 Fax: +971 (0)4 326 2733
 E-mail: terraco@terraco.ae
 Web: www.terraco.com

UK:

ADDAGRIP
 Tel: +44 (0)1825 761 333
 Fax: +44 (0)1825 768 566
 E-mail: sales@addagrip.co.uk
 Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 3 820 100
 Fax: +84 (0)650 3 820101
 E-mail: terraco@terraco.com.vn
 Web: www.terraco.com