

OVERVIEW

Maxi Tile Grout is a hard-wearing, water-resistant grout for filling joints in exterior and interior walls and floor ceramic tiles, mosaics and clinkers. It is specially formulated to fill joints of up to 5 mm width. It is easily applied by hand. Maxi Tile Grout is manufactured in a range of 17 standard colours.

PROPERTIES

Maxi Tile Grout is composed of precisely graded, pure-crystalline, marble powder, a blend of special cements, water-repellent materials and plasticizers. Maxi Tile Grout does not curl up during application and gives a water- and weather-resistant joint with no shrinkage cracks.

AREAS OF USE

Maxi Tile Grout can be used on materials such as ceramic wall and floor tiles, clinkers and mosaics, where joints do not exceed 5 mm in width. It is applicable for interior floors and walls, exterior floors and walls, bathrooms, kitchens, roofs etc.

PREPARATION OF SURFACE

Ensure that all tile joints and edges are free and clean of excess tile fixing mortar and foreign matter.

MIXING

Thoroughly mix Maxi Tile Grout with 30-32% water using a mechanical stirrer for 2-3 minutes. Let it stand for 5 minutes, re-stir and apply.

APPLICATION

Wait until the tile adhesive has set (approx. 24 hours) before grouting. Apply Maxi Tile Grout diagonally into the joints with a rubber edged spatula. Remove excess grout with a moist sponge before drying.

Do not apply Maxi Tile Grout to areas larger than those which can be completed within an hour. Porous tiles should be moistened with water before grouting.

After Maxi Tile Grout has dried and before it has hardened, polish the tiles with a clean, dry cloth leaving the joints flush with the tile. Moisten the joints with a wet sponge 24 hours after grouting.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Maxi Tile Grout is supplied in powder form – 2 kg plastic bags (carton of 10 bags x 2 kg each). White and grey colours are also supplied in 10 kg and 25 kg craft bags.

Maxi Tile Grout should be stored unopened in a clean, cool, dry area protected from direct sunlight. Original unopened sacks can be stored up to 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Tile grouting compound for joints up to 5 mm.
Filler	Crushed, precisely graded extenders.
Colours	17 standard colours.
Binders	Hydraulic and organic.
Material Consumption	0.5 - 1.0 kg per m ² depending upon width of tile joints.
Mixing	0.6 litre water per 2 kg bag 3.0 litre water per 10 kg bag 7.5 litre water per 25 kg bag.
Packaging	2 kg plastic bags (carton of 10 bags x 2kg – for colours), 10kg and 25kg paper bags (White and Grey).
Storage	12 months when stored in normal, dry condition in unopened bags.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.

Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 1 2819 045
Fax : +353 (0) 1 2819 048
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terrakovostok.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com