

OVERVIEW

TimberLac is an interior acrylic wood varnish which is both easy to use and quick drying. TimberLac is available as a clear finish in gloss, satin and matt. If colour is required TimberStain is first used to stain the wood, after which TimberLac is applied in 2 to 3 coats. The full job can be completed in 1 day due to its fast drying nature. Clean-up is with water.

PROPERTIES

TimberLac is an acrylic based lacquer coating for interior wood with the following properties:

- Tough durable finish
- Quick drying
- 3 coat application in 1 day
- Easy to apply

AREA OF USE

All interior wood subject to medium to light wear.

PREPARATION OF SURFACE

Remove all traces of grease, wax or polish by washing with white spirits. On new surfaces ensure that nails are punched below surface and all holes are filled with suitable wood filler. Sand in the direction of grain and remove any dust with a lint free cloth.

PRODUCT GRADES/CODES

Gloss	62610
Satin	62612
Matt	62614

STAINING

If colour is required use TimberStain. See data sheet for application instructions.

APPLICATION & CLEANING OF TOOLS

Stir thoroughly before use. Apply using a brush or short pile roller finishing in the direction of the grain. Leave for 2 to 4 hours between coats. Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

TimberLac is supplied in 1ltr, 2.5ltr, 5ltr and 20ltr containers.

TimberLac should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic quick drying interior wood varnish.
Sheen	Gloss, satin and matt..
Colour	Clear.
Binder	Acrylic .
Clean-up	With water.
Touch Dry	1 to 2 hours.
Re-coat	2 to 4 hour.
Coverage	New wood 50-100 grs/m ² . Previously coated 40-50 grs/m ²
Packaging	1ltr, 2.5ltr and 5ltr containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8759 4742
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18
Fax: +86 (0)21 625205 47
Email: sales@terraco.com.cn
Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58
Fax: +20 (0)22 29184 80
E-mail: terraco@terraco.com.eg
Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: technical-centre@terraco.com
Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8
Fax: +92 (0)42 3529 70 55
Email: terraco@terraco.pk
Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133
Fax: +40 (0)318 148 810
E-mail: ahaque@terraco.com
Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237
Fax: +7 (0)495 6273 881
E-mail: adm@terraco.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
Fax: +7 (0)4212 410591
E-mail: terracovostok@terraco.khn.ru
Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551
Fax: +82 (0)2 5671 771
E-mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58
Fax: +66 (0)2 946 68 59
E-mail: terraco@terraco.co.th
Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699
Fax: +971 (0)4 326 2733
E-mail: terraco@terraco.ae
Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333
Fax: +44 (0)1825 768 566
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100
Fax: +84 (0)650 3 820101
E-mail: terraco@terraco.com.vn
Web: www.terraco.com